

Serial No. 10/727,880

AMENDMENT TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS

Claim 1 (currently amended): A nozzle structure of a lawn sprinkler, said nozzle structure comprising:

a nozzle piece provided with a plurality of water emission holes;

~~a guide seat provided at one end with a fastening portion and a fitting portion, said guide seat further provided at other end with a tapered portion, said fastening portion being used to hold securely said nozzle piece; and~~

~~a receptacle provided at one end with an opening, and in an interior of other end thereof with a locating portion, said receptacle being used to hold said guide seat in such a way that said tapered portion of said guide seat is located by said locating portion of said receptacle, and that said fitting portion of said guide seat is fitted into said opening of said receptacle;~~

~~wherein said guide seat is further provided at the one end with a leakproof flange whereby said leakproof flange is located between said fastening portion and said fitting portion of said guide seat such that said opening of said receptacle is sealed off by said leakproof flange~~

a receptacle having a first end having an inside provided with an opening and a second end having an inside provided with a locating portion; and

a guide seat mounted between said nozzle piece and said receptacle and having a first end having a peripheral wall provided with a fastening portion securely mounted on said nozzle piece and a fitting portion closely fitted into said opening of said receptacle, and a second end having a peripheral wall provided with a tapered portion located by said locating portion of said receptacle;

Serial No. 10/727,880

wherein the peripheral wall of the first end of said guide seat is further provided with a leakproof flange located outside of said opening of said receptacle and enclosed around an end wall of said opening of said receptacle to closely seal said opening of said receptacle.

Claim 2 (new): The nozzle structure as claimed in claim 1, wherein said leakproof flange of said guide seat is located between said fastening portion and said fitting portion and has an outer diameter greater than that of said fitting portion.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.